

TAGSYS RFID™
e-connecting goods

www.tagsysrfid.com

Product

OEM MID-RANGE READER

TAGSYS Medio™ P013

- Powerful
- Small footprint
- print Low cost



The TAGSYS Medio™ P013 is a low cost 13.56 MHz RFID OEM reader for mid-range reading applications. It communicates using an RS232/RS422/RS485 serial communication link. The TAGSYS Medio™ P013 can operate either in standard mode or in standalone mode. One industrial input and output can be used in both operating mode.

TAGSYS is the global leader in item-level RFID infrastructure. **TAGSYS** RFID provides RFID systems for end-to-end item-level tracking that automates labor-intensive processes, authenticates and safeguards goods, and enables real-time inventory and asset visibility.
With a proven track record of delivering Reliable, Accurate and Secure (RAS) RFID systems and tags, **TAGSYS** has deployed over 50 million tags and 50,000 reader systems to over 500 customers in more than 40 countries.
TAGSYS RFID solutions are currently being deployed in a range of highly specialized vertical markets that include pharmaceutical, fashion apparel, libraries, and textile rental. The company is headquartered in France's Smart Valley with offices in the USA (Doylestown, Pennsylvania) and Asia (Hong Kong).
More information on **TAGSYS** can be found at **http://www.tagsysrfid.com**

TECHNICAL SPECIFICATIONS

RF Output Power	1 W
Chip compatibility	C210, C240
Communication Interface	RS232/RS422/RS485
Size	90 X 60 mm (3.5 x 2.3 inches)

©TAGSYS 2006